

# EdgePro® Rigid Paver Restraint



## Product Configurations

Item 1303	EdgePro® Rigid	7.5' Bundled
Item 1323	EdgePro® Rigid	15' Bundled

## Product Specifications

Material:	Engineered Rigid PVC Alloy
Weight:	0.50 lbs. per linear foot (nominal)
Vertical Wall Height:	1.75 in. (nominal)
Horizontal Base Width:	3.50 in. (nominal)
Vertical Wall Thickness:	0.14 in. (nominal)
Horizontal Base Thickness:	0.14 in. (nominal)



Intended for  
60-80mm paver thicknesses

## Packaging Specifications

12 – 7.5' lengths/bundle, 48 bundles/pallet (4,320 ft.)  
6 – 15' lengths/bundle, 50 bundles/pallet (4,500 ft.)

## Physical Property Testing

Impact Strength	ASTM Test D-256	Min. 120 lbs./in.
Tensile Strength	ASTM Test D-638	Min. 5,000 PSI
Flexural Modules	ASTM Test D-790	Min. 280,000 PSI

EdgePro® Paver Restraint products pass Ultraviolet and Weathering Tests per Federal Std. 191 A Method 5804.

## Paver Restraint Accessories

Steel Stakes  
60-Count




Item 1900

8" Spiral  
Steel Spikes  
50# Case



SPIKE8BS

10" Spiral  
Steel Spikes  
50# Case




SPIKE10BS

10" Round  
Steel Spikes  
50# Case




SPIKE10BR

12" Round  
Steel Spikes  
50# Case




SPIKE12BR

10" Spiral  
Nylon Spikes  
150-Count



SPIKE10NS

10" Round  
Nylon Spikes  
150-Count



SPIKE10NR



## Dimex Limited Lifetime Warranty

EdgePro® Paver Restraint products are guaranteed to be free from manufacturing defects and will not crack, rot, or deteriorate when handled and installed according to recommended guidelines.



28305 State Route 7  
Marietta, OH 45750  
www.edgepro.com

Phone: 740-374-3100  
Toll Free: 800-334-3776  
Fax: 740-374-5420